



## Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)  
IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T;  
IEEE 802.5 16 MB; ISDN; TPDDI; ATM

## Standards

EN 50173-1; EN 50288-3-1  
ISO/IEC 11801; IEC 61156-5  
TIA/EIA-568-B.2

## Flame resistance

LSHF(LSOH): IEC 60332-1; IEC 60754-2; IEC 61034

## Construction

Conductor	bare copper wire, $\varnothing$ 0.51 mm (AWG24)
Insulation	PE, $\varnothing$ 1.0 mm
Twisting	2 cores to the pair
Cable lay up	4 pairs to the core
Screen	Al-laminated plastic foil, Drain wire AWG26 tinned
Sheath	LSHF(LSOH), grey RAL 7035

## Mechanical properties

Bending radius

without load	$\geq 25$ mm
--------------	--------------

with load	$\geq 50$ mm
-----------	--------------

Temperature range

during operation	-20°C to + 60°C
------------------	-----------------

during installation	0°C to + 50°C
---------------------	---------------

**Electrical properties****at 20°C±5°C**

Loop resistance		≤ 190Ω/km
Resistance unbalance		≤ 2%
Insulation resistance	(500 V)	≥ 2000 MΩxkm
Mutual capacitance	At 800 Hz	Nom. 48 nF/km
Capacitance unbalance	(pair/ground)	≤ 1500 pF/km
Characteristic impedance	(1-100 MHz)	(100 ± 15) Ω
Nominal velocity of propagation		ca. 67%
Propagation delay		≤ 535 ns/100 m
Delay skew		≤ 20 ns/100 m
Test voltage	(DC, 1 min) core/core and core/screen	1000 V
Transfer impedance	at 1 MHz	≤ 50 mΩ/m
	at 10 MHz	≤ 100 mΩ/m
	at 30 MHz	≤ 200 mΩ/m

**Electrical data (nominal)****acc. to Cat.5e (at 20°C)**

F (MHZ)	Attenuation (dB/100m)	NEXT (dB)	PS-NEXT (dB)	ACR (dB/100m)	PS-ACR (dB/100m)	ELFEXT (dB/100m)	PS-ELFEXT (dB/100m)	Return loss (dB)
1.0	1.9	71	68	69.1	66.1	68	65	20
4.0	3.7	62	59	58.3	55.3	56	53	23
10.0	6.0	56	53	50.0	47.0	48	45	25
16.0	7.6	53	50	45.4	42.4	44	41	25
20.0	8.5	51	48	42.5	39.5	42	39	25
31.2	10.7	49	46	38.3	35.3	38	35	24
62.5	15.7	44	41	28.3	25.3	32	29	22
100.0	19.8	41	38	21.2	18.2	28	25	20
125.0	22.3	40	37	17.7	14.7	26	23	19
155.5	24.2	38	35	13.8	10.8	24	21	
175.0	25.7	37	34	11.3	8.3	23	20	
200.0	27.5	36	33	8.5	5.5	22	19	
250.0	29.2	35	32	5.8	2.8	20	17	
300.0	32.0	34	31	2.0	-1.0	16	13	

**Technical data**

Product code	Designation	Brand name	Colour	Outer diameter mm	Fire load		Weight netto kg/km	Copper content	Tensile force
					MJ/km	kWh/m			
KE300S24LSOH	F/UTP 4x2x0.51AWG24	KELine	grey	5.9	396	0.110	37	19.8	80