



Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)
IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T;
IEEE 802.5 16 MB; ISDN; TPDDI; ATM

Standards

EN 50173-1; EN 50288-3-1
ISO/IEC 11801; IEC 61156-5
TIA/EIA-568-B.2

Construction

Conductor	bare copper wire, \varnothing 0.51 mm (AWG24)
Insulation	PE, \varnothing 1.0 mm
Twisting	2 cores to the pair
Cable lay up	4 pairs to the core
Screen	Al-laminated plastic foil, Drain wire AWG26 tinned
Inner sheath	PVC
Outer sheath	PE, black

Mechanical properties

Bending radius

Temperature range

without load	≥ 25 mm
with load	≥ 50 mm
during operation	-20°C to + 75°C
during installation	0°C to + 50°C

KELine[®]
Cable**F/UTP 4x2x0.51(AWG24) CAT.5E OUT**
100Ω Data Cable ISO/IEC 11801 CAT.5e**F/UTP****Electrical properties****at 20°C±5°C**

Loop resistance		≤ 190Ω/km
Resistance unbalance		≤ 2%
Insulation resistance	(500 V)	≥ 2000 MΩxkm
Mutual capacitance	At 800 Hz	Nom. 48 nF/km
Capacitance unbalance	(pair/ground)	≤ 1500 pF/km
Characteristic impedance	(1-100 MHz)	(100 ± 15) Ω
Nominal velocity of propagation		ca. 67%
Propagation delay		≤ 535 ns/100 m
Delay skew		≤ 20 ns/100 m
Test voltage	(DC, 1 min) core/core and core/screen	1000 V
Transfer impedance	at 1 MHz	≤ 50 mΩ/m
	at 10 MHz	≤ 100 mΩ/m
	at 30 MHz	≤ 200 mΩ/m

Electrical data (nominal)**acc. to Cat.5e (at 20°C)**

F (MHZ)	Attenuation (dB/100m)	NEXT (dB)	PS-NEXT (dB)	ACR (dB/100m)	PS-ACR (dB/100m)	ELFEXT (dB/100m)	PS-ELFEXT (dB/100m)	Return loss (dB)
1.0	1.9	71	68	69.1	66.1	68	65	20
4.0	3.7	62	59	58.3	55.3	56	53	23
10.0	6.0	56	53	50.0	47.0	48	45	25
16.0	7.6	53	50	45.4	42.4	44	41	25
20.0	8.5	51	48	42.5	39.5	42	39	25
31.2	10.7	49	46	38.3	35.3	38	35	24
62.5	15.7	44	41	28.3	25.3	32	29	22
100.0	19.8	41	38	21.2	18.2	28	25	20
125.0	22.3	40	37	17.7	14.7	26	23	19
155.5	24.2	38	35	13.8	10.8	24	21	
175.0	25.7	37	34	11.3	8.3	23	20	
200.0	27.5	36	33	8.5	5.5	22	19	
250.0	29.2	35	32	5.8	2.8	20	17	
300.0	32.0	34	31	2.0	-1.0	16	13	

Technical data

Product code	Designation	Brand name	Colour	Outer diameter mm	Weight netto kg/km	Copper content	Tensile force
KE300S24OUT	F/UTP 4x2x0.51AWG24	KELine	black	8.4	46	19.8	82